

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

(12) UK Patent Application (19) GB (11) 2 265 350 (13) A

(43) Date of A publication 29.09.1993

(21) Application No 9305024.3

(22) Date of filing 11.03.1993

(30) Priority data

(31) 9206501 (32) 25.03.1992 (33) GB


(71) Applicant
Fiomat Limited

(Incorporated in the United Kingdom)

Unit 2, Peakdale Road, Brookfield, Glossop,
Derbyshire, SK13 9LQ, United Kingdom(72) Inventor
Barrie Armstrong Poulton(74) Agent and/or Address for Service
McNeight & Lawrence
Regent House, Heaton Lane, Stockport, Cheshire,
SK4 1BS, United Kingdom(51) INT CL⁵
B65B 63/04(52) UK CL (Edition L)
B8C CF15(56) Documents cited
GB 1348974 A GB 1248533 A GB 1112203 A
GB 0961473 A(58) Field of search
UK CL (Edition L) B8C CB19 CB3 CF10 CF15 CF17
CU19
INT CL⁵ B65B 13/18 27/08 63/04



(54) Bag folder

(57) A machine for folding bags (particularly emptied FIBC's) comprises a spool 16 with which one end of a bag can be engaged, means 21 for rotating the spool and means 23 for constraining the bag to be wound onto the spool as it is rotated. The spool 16 comprises two tines 17, 18 so that the bag is wound thereon to form a roll of flattened shape. The bag rests on parallel horizontal rails 22 and is constrained by arcuate rail 23 as it is drawn onto the spool. The base of the machine comprises hoppers 13, 14 to collect any residual particulate material released by the bag, such material being extracted by a suction line 15. The folded bags may be baled and returned to be refilled.



GB 2 265 350 A

1/2






FIG. 3

BAG FOLDER

This invention concerns a machine for folding intermediate bulk containers in the form of large bags used for the transport of powdered, granulated or other particulate solid materials.

Such containers will be referred to hereinafter simply as "bags".

Bags are frequently intended for re-use and are returned from the sites where they are emptied to the sites where they are filled. When they have been emptied they are filled with air and very bulky and it is necessary to squeeze the air from them and fold them up into conveniently sized packages which can be baled for their return journeys. Such packaging is equally desirable if the bags are to be transported for disposal.

Generally operators fold the bags, which can be 2m in length by placing them on the floor and manipulating them with hands and feet. Aside from the generally inconvenient and time-consuming nature of this operation, residual particulate material adhering to the bags is released into the atmosphere and the outsides of the bags can become grossly contaminated.

It is an object of the present invention to provide a machine for folding bags and which eliminates to a substantial extent the problems aforesaid.

According to the present invention there is provided a machine for folding bags comprising a spool with which one end of a bag can be engaged, means for rotating the spool and means for constraining the bag to be wound onto the spool as it is rotated.

The spool may be shaped so that the wound bag is in the shape of a flat package.

The constraining means may comprise an arcuate member such as a rail spaced from the envelope described by the spool as it is rotated.

Guide means comprised by spaced longitudinal rails arranged in a horizontal plane may provide a bed upon which a bag may be laid and from which it is drawn as it is wound onto the spool.

The base of the machine may comprise one or more hoppers to collect any particulate material released by the bag whilst it is manipulated by the machine.

Suction extraction means may be connected with the base of the or each hopper.

The invention will be further apparent from the following description, with reference to the several figures of the accompanying drawings, which show, by way of example only one form of bag folding machine embodying same.

Of the drawings :-

Figure 1 shows a longitudinal cross-section through the machine on the line I-I of Figure 2;

Figure 2 shows a transverse cross-section through the machine on the line II-II of Figure 1; and

Figure 3 shows a plan view of the machine.

Referring now to the drawings it will be seen that the machine comprises an open-topped casing generally indicated at 10 and consisting of two sections 11 and 12 arranged end-to-end each having a base in the form of a hopper 13 and 14 respectively from which collected materials can be extracted by a suction line 15.

At one end of the casing is a spool 16 comprised by a pair of diametrically spaced tines 17 and 18

extending horizontally from a circular plate 19 which is mounted for rotation about its centre by means of a chain drive 20 connected with a winding handle 21.

Three transversely spaced rails 22 extend generally upwardly from the end of the casing 10 remote from the spool and then horizontally towards the spool 16 and form a bed upon which a bag to be folded may be laid.

The central rail 22 has an arcuate extension 23 spaced from the envelope described by the tines 17 and 18 as the spool 16 is rotated.

In use, a bag is laid within the casing on the rails 22 and one of its ends is engaged with the spool 16 which is rotated by means of the handle 21. The bag is constrained by the extension 23 to be wound tightly around the tines 17 and to form a generally flat package, which may upon completion be slid from the tines for packaging.

Any particulate material released from the bag into the hoppers 13 and 14 is collected into the line 15 reducing release into the environment.

It will be appreciated that it is not intended to limit the invention to the above example only, many variations, such as might readily occur to one skilled in the art, being possible, without departing from the scope thereof.

Thus the machine may be equipped with automatic means to discharge the wound up bags directly into such as a baling machine.

The spool may be at an elevated position whereby the bag is arranged vertically rather than horizontally before being taken onto the spool.

CLAIMS

1. A machine for folding bags comprising a spool with which one end of a bag can be engaged, means for rotating the spool and means for constraining the bag to be wound onto the spool as it is rotated.
2. A machine according to claim 1, wherein the spool is shaped so that the wound bag is in the shape of a flat package.
3. A machine according to claim 1 or claim 2, wherein the constraining means comprises an arcuate member such as a rail spaced from the envelope described by the spool as it is rotated.
4. A machine for folding bags according to any preceding claim, wherein guide means comprised by spaced longitudinal rails arranged in a horizontal plane provide a bed upon which a bag may be laid and from which it is drawn as it is wound onto the spool.
5. A machine according to any preceding claim, wherein the base of the machine comprises by at least one hopper to collect any particulate material released by the bag whilst it is manipulated by the machine.

6. A machine according to claim 5, wherein suction extraction means is connected with the base of the hopper.

Patents Act 1977
Examiner's report to the Comptroller and
Secretary 17 (The Search Report)

Application number

GB 9305024.3

Relevant Technical fields

(i) UK Cl (Edition 1)) B8C (CB3, CB19, CF10, CF15, CF17, CU19)

(ii) Int Cl (Edition 5)) B65B 13/18, 27/08, 63/04

Databases (see over)

(i) UK Patent Office

(ii)

Search Examiner

S R SMITH

Date of Search

21 APRIL 1993

Documents considered relevant following a search in respect of claims 1 TO 6

Category (see over)	Identity of document and relevant passages	Relevant to claim(s)
X	GB 1348974 (PAPER CONVERTING) see lines 26 to 37 of page 1	1,2
X	GB 1248533 (NIDECKER) see Claim 1 and Figure 1	1,3
X	GB 1112203 (HELIOT) see lines 98 to 114 of page 3	1,2
X	GB 961473 (SCHULTE) see lines 1 to 34 of page 3	1,2

Category	Identity of document and relevant passages	Relevant to claim(s)

Categories of documents

X: Document indicating lack of novelty or of inventive step.

Y: Document indicating lack of inventive step if combined with one or more other documents of the same category.

A: Document indicating technological background and/or state of the art.

P: Document published on or after the declared priority date but before the filing date of the present application.

E: Patent document published on or after, but with priority date earlier than, the filing date of the present application.

&: Member of the same patent family, corresponding document.

Databases: The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).